


## CERAMIC DRIVER



**C51-6-286**  
CERAMIC TWEETER DRIVER

WERKSTOFF	Ceramic
ANWENDUNG	Tweeter
OVERALL DIAMETER	85.6 mm
CUTOUT DIAMETER/SQUARE	86 mm
OVERALL DEPTH	87 mm
MOTOR ASSEMBLY DEPTH	0 mm
MOTOR ASSEMBLY DIAMETER	0 mm

## VOICE COIL PARAMETERS

SPEZIFIKATION		WERT	EINHEIT
POWER HANDLING	P	120	Watt
LINEAR EXCURSION	Xmax	+ / - 0.8	mm
VOICE COIL DIAMETER		0	mm
VOICE COIL FORMER MATERIAL		Ti	
VOICE COIL MATERIAL		Cu	
VOICE COIL INDUCTANCE	Le	0	mH
FORCE FACTOR	Bl	0	N/A
MOTOR TYPE		unterhängig	
FERROFLUID FILLING		nein	


## MECHANICAL DATA

SPEZIFIKATION		WERT	EINHEIT
OVERALL DIAMETER		85.6	mm
CUTOUT DIAMETER/SQUARE		86	mm
MIN. FRONTPLATE THICKNESS		7	mm
OVERALL DEPTH		87	mm
MOTOR ASSEMBLY DEPTH		0	mm
MOTOR ASSEMBLY DIAMETER		0	mm
SCREWFITTING			mm
TERMINAL		+: 4.8 x 0.8 / -: 2.8 x 0.8	mm
SHIPPING WEIGHT / NET WEIGHT		2.30	kg
SHIPPING BOX SIZE		220 x 115 x 115	mm


## THIELE/SMALL PARAMETERS

SPEZIFIKATION		WERT	EINHEIT
SENSITIVITY (2.83V / 1M)	Lp	93	dB
DC-RESISTANCE	Re	5.3	Ohm
RESONANCE FREQUENCY	Fs	550	Hz
EQUIVALENT VOLUME OF AIR	Vas		L
MECHANICAL Q	Qms	4.56	
ELECTRICAL Q	Qes	1.59	
TOTAL Q	Qts	1.18	
EFFECTIVE PISTON AREA	Sd	0	cm <sup>2</sup>
MOVING MASS	Mms	0	g
SUSPENSION COMPLIANCE	Cms	0	mm/N
MECHANICAL RESISTANCE	Rms	0	kg*s


## FREQUENCY RESPONSE [DB]



## IMPEDANCE [OHM]



## HARMONIC DISTORTION [%]



© 2017 THIEL & PARTNER GMBH - ALL RIGHTS RESERVED - ALL DATA WITH RESERVATION AND SUSPECT TO CHANGE.