



# CAT 378

## Classic Advanced Tweeter, Ø 94mm, 8Ω

### Features:

- \* 94mm horn-loading face plate
- \* Large Hexatech™ aluminum voice coil
- \* Replaceable Acuflex™ dome / coil assembly
- \* High sensitivity
- \* High power handling
- \* Sturdy gold plated input tags



## SPECIFICATIONS

### General Data

Overall Dimensions	DxH	94mm(3.70")x59mm(2.32")
Nominal Power Handling (DIN)	P	200W
Transient Power 10ms		1000W
Sensitivity 2.83V/1M		93dB SPL
Frequency Response		See graph
Dome Material		Acuflex™ hand coated soft dome
Net Weight	Kg	0.555

### Electrical Data



Nominal Impedance	Z	8Ω
DC Resistance	Re	5.2Ω
Voice Coil Inductance @ 1KHz	LBM	0.09mH

### Voice Coil and Magnet Parameters



Voice Coil Diameter	DIA	28mm
Voice Coil Height		2.7mm
HE Magnetic Gap Height	HE	2.5mm
Max. Linear Excursion	X	
Voice Coil Former		Aluminum
Voice Coil Wire		Hexatech™ Aluminum
Number Of Layers		2
Magnet System Type		Ferrite vented
B Flux Density	B	1.5 T
BL Product	BXL	3.5 N.A

### T-S Parameters

Suspension Compliance	Cms	
Mechanical Q Factor	Qms	
Electrical Q Factor	Qes	
Total Q Factor	Qts	
Mechanical Resistance	Rms	
Moving Mass	Mms	0.44 g
Eq. Cas Air Load (liters)	VAS	
Resonant Frequency	Fs	700 Hz
Effective Piston Area	SD	6.0 cm <sup>2</sup>



- A - Overall diameter 94mm
- B - Magnet/Chamber diameter 72mm
- C - Flange thickness 4mm
- D - Overall height 59mm
- E - Magnet/Chamber depth 55mm
- F - Mounting holes location diameter 86mm
- G - 3 Mounting holes, at 120° interval, inner hole diameter Ø 3.7mm, pocket h 1mm, Ø 8mm



Measured on IEC baffle using Bruel & Kjaer 3144 model microphone.

Morel operate policy of continuous product design improvement, consequently specifications are subject to alteration without prior notice.